

E 9-E

96.23

574.2  
-003  
5A  
584.10

-001  
25.00F.

825  
856.88  
-002  
10.10F.

To be used for  
-007 By Lorraine  
24.85F.

1069.86

RD  
60

-003  
1.00F.  
465

-010  
7.67A.

634.37  
633.77

1839.42  
1846.68

-013  
22.78A.

465  
-005 1.37A  
465  
839.96  
-009 2.51A  
832.96

-016  
7.60A.

500

738.54

-006  
7.22F.

-014  
1.61A.

-001 .54F.

-002  
9.96F.

-017  
4.71A.

-001  
5.36F.

SEP 10 1976  
JUN 15 1976

-013  
20.80A.

APPROVED  
LORAIN CO.  
MAP DEPT.

DATE 5-22-76

PAGE 1/1A

BY L.W. HARRIS

VOID  
AFTER

021  
10.00A.

-003  
19.75F.

022  
9.75"

-015  
5.03A.

-014  
5.27A.

248.82  
-004  
1.00F.  
148.50

142.22  
142.86  
142.55

434.47  
384.02

-006  
7.71A

able)

RD

890.73  
-001  
0.07A.

-002  
13.43F.

-001  
5.89F.

-013  
6.5A.

6.22F.

9.05  
6.22 A.

20