

metric units

19mm (3/4") BY 760MM (30 INCH) REINFORCING BAR WITH AN ALUMINUM CAP OF MINIMUM DIAMETER OF 38MM (1-1/2 INCH) STAMPED "O" DOT R/W CENTRAL ENGINEERING P.S.6306"

ADJUSTABLE CENTERLINE MONUMENT

EXISTING MONUMENT BOX

R.R. SPIKE SET

R.R. SPIKE FOUND

O.D.H. SET

P.K. SET

LEGEND

19mm (3/4") BY 760MM (30 INCH) REINFORCING BAR WITH AN ALUMINUM CAP OF MINIMUM DIAMETER OF 38MM (1-1/2 INCH) STAMPED "O" DOT R/W CENTRAL ENGINEERING P.S.6306"

ADJUSTABLE CENTERLINE MONUMENT

EXISTING MONUMENT BOX

R.R. SPIKE SET

R.R. SPIKE FOUND

O.D.H. SET

P.K. SET

NOTES

1. FOR CENTERLINE MONUMENT NOTES AND LOCATIONS, SEE SHEET 1 OF 4.

2. THE S.R. 301 CENTERLINE BEARINGS ARE TAKEN FROM THE LOR-301 CENTERLINE ALIGNMENT INFORMATION PROVIDED BY THE O.D.O.T. SURVEY DEPARTMENT, DISTRICT 3 (DATED 7-29-97) AND THE CENTERLINE SURVEY PLAN FOR LOR-611-8.66 AS RECORDED IN PLAT VOLUME 46, PAGE 76 AND 77, OF THE LORAIN COUNTY RECORDS.

3. THE EXISTING RIGHT OF WAY WIDTH AND LOCATION WERE DETERMINED FROM EXISTING O.D.O.T. PLANS FOR LOR-611-8.66 DATED 7-16-93.

4. ALL DIMENSIONS ARE IN METERS UNLESS INDICATED OTHERWISE.

THE METRIC TO ENGLISH CONVERSION FACTOR IS BASED ON THE U.S. SURVEY FOOT AND IS:

1 FOOT = 1200/3937 METERS = 0.3048006096 METERS

1 METER = 3.2808333333 FEET.

END R/W ACQUISITION
STA. 40+757.114
SLD 40.757

END WORK
STA. 40+746.562

END PROJECT
STA. 40+722.969
SLD 40.723

REVISION
03-13-03

APPROVED
LORAIN COUNTY ENGINEERING
DATE 4/17/03

PAGE 3-00-007-A
BY: HATFIELD
#03-01340

PHS 3-10-03	NAME - PAR. 1	DESCRIPTION
REV. DATE		
PLAN COMPLETION DATE:	OCTOBER 30, 2001	

