

SHERMAN P. MASON  
V. 722 P. 662



I.P. Fd. & Used  
for line 0.61'S.

SEC. 24

SEC. 25

-040

5.9968 Ac.

RICHARD D. & PAT JORDAN  
V. 931 P. 616

5.89°42'10"W.

285.00'

I.P. Set

313.04'

298.58'

I.P. Set

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

936.30' ±

711.30'

5.0°14'20"E

7.89°42'10"E  
25.00'

I.P. Set

I.P. Set

5.0°14'20"E

225.00'

5.0°14'20"E

225.00'

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Fd.

31.16' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

I.P. Set

30.00' ±

N. 89°42'10"E. 1829.66' meas. (1829.17' Cty.)

PARSONS ROAD 60'

M.B./I.P. Fd. & Used  
for E

554.55 m.

260.00'

R.R. Spike Fd.  
0.15' S. of E

M.B./I.P. Fd. &  
Used for E

SURVEY FOR

PAUL W. Sr. & GAIL J. STANG

PART OF ORIGINAL SECTION 25 IN CARLISLE TOWNSHIP

LORAIN COUNTY OHIO

SCALE 1"=100' APRIL, 1992

BY LAUNDON • SIMON • CAHL & ASSOC.

ENGINEERS SURVEYORS

110 MIDDLE AVE. ELYRIA, O. 44035

JOB No 92-2180 FB 223 P 34

10-00-025-101-040

10-00-025-E

4520

270